

ALLOY SHUTTERS FOR COMMERCIAL PROPERTY

Curtain


Manufactured from 18swg (1.2mm) thick 89mm extruded aluminium flat Solid or Punched interlocking laths fitted with Nylon end shoes to alternate laths down both edges to prevent lateral movement. The bottom rail is manufactured from an 18swg thick extruded aluminium 'T' or 'L' section.

Guides

Constructed from 50mm deep x 32mm wide x 3mm thick extruded aluminium channel. For face fit applications, the channels may be bolted to angle section or box section. End Plates fabricated from 3 or 6mm plate are generally or bolted to the guide assemblies to provide support for the Barrel.

Barrel

Constructed from various sizes of steel Circular Hollow Section containing either high tensile helical counterbalance springs (for manually operated shutters) or a 240v single phase tubular motor (for electrically operated shutters). A Safety brake to comply with BS EN 13241:2003 is also fitted to electrically operated shutters when the opening will be used by personnel.



Operation

Either manually operated (push up/pull down) or electrically operated via a 240v single phase internal tubular motor with hand crank manual override.

Finishes

The standard finish is natural mill finish aluminium. Anodised finish in a range of shades/colours or Polyester Powder Coat paint finish is also available in most RAL, BS4800 or BS381C range colours at additional cost.



SECURI-DOORS
SERVICES LIMITED

9 STANBOROUGH MEWS
WELWYN GARDEN CITY
HERTFORDSHIRE
AL8 6DB

INFO@SECURI-DOORS.CO.UK
WWW.SECURI-DOORS.CO.UK

01707 886887