

ROLLER GRILLES FOR COMMERCIAL PROPERTY

Curtain

Constructed from mill finish aluminium tubes and links arranged over 8mm diameter solid galvanised steel rods to form a 230mm x 70mm brick-bond pattern. The bottom rail is manufactured from purpose made 3mm thick extruded mill finish aluminium 'T' section.

Guides

Constructed from 65mm deep x 32mm wide x 3mm thick steel channel bolted to steel angle section or steel box section. End Plates fabricated from 3 or 6mm steel plate are generally welded or bolted to the angle or box section to support the Barrel.

Barrel

Constructed from various sizes of steel Circular Hollow Section containing either high tensile helical counterbalance springs (for manually operated shutters) or a 240v single phase tubular motor (for electrically operated shutters). A Safety brake to comply with BS EN 13241:2003 is also fitted to electrically operated shutters when the opening will be used by personnel.



Operation

Either manually operated (push up / pull down) or electrically operated via a 240v single phase internal tubular motor with hand crank manual override.

Finishes

The standard finish is natural mill finish aluminium to the grille curtain and galvanised finish to the guides and coil casing (if fitted). Polyester Powder Coat paint finish is also available in most RAL, BS4800 or BS381C range colours. 12 Months or 250,000 cycles, parts and labour excluding damage not caused by normal operation.



SECURI-DOORS
SERVICES LIMITED

9 STANBOROUGH MEWS
WELWYN GARDEN CITY
HERTFORDSHIRE
AL8 6DB

INFO@SECURI-DOORS.CO.UK
WWW.SECURI-DOORS.CO.UK

01707 886887